according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 08-May-2015 **Print date:** 27-May-2015

Version: 1 Page 1/11



HTC Stain Protection

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name/designation:

HTC Stain Protection

1.2. Relevant identified uses of the substance or mixture and uses advised against Use of the substance/mixture:

Impregnating agent

1.3. Details of the supplier of the safety data sheet

Supplier (manufacturer/importer/only representative/downstream user/distributor):

HTC Sweden AB

P.O Box 69

614 22 Söderköping

Sweden

Telephone: +46(0)121/294-00 **Telefax:** +46(0)121/152-12 **E-mail:** info@htc-sweden.com

Website: www.htc-floorsystems.com

E-mail (competent person): charlotte.uhrbom@htc.se

1.4. Emergency telephone number

24h: +49(0)89-19240

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]:

Hazard classes and hazard categories		Classification pro- cedure
flammable liquids <i>(Flam. Liq. 2)</i>	H225: Highly flammable liquid and vapour.	
Serious eye damage/eye irritation (Eye Irrit. 2)	H319: Causes serious eye irritation.	

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms:





GHS02 Flame

GHS07 Exclamation mark

Signal word: Danger

Hazard components for labelling:

toluene; methanol; trimethoxy(methyl)silane

hazard statements	for physical hazards
H225	Highly flammable liquid and vapour.

hazard statements	for health hazards
H319	Causes serious eye irritation.

Supplemental Hazard information (EU): -

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 08-May-2015 Print date: 27-May-2015

Version: 1 Page 2/11



HTC Stain Protection

Precautionary s	Precautionary statements Prevention			
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.			
P243	Take precautionary measures against static discharge.			
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.			
P271	Use only outdoors or in a well-ventilated area.			
P280	Wear protective gloves/protective clothing/eye protection/face protection.			

Precautionary statements Response		
P305 + P351 +	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present	
P338	and easy to do. Continue rinsing.	

2.3. Other hazards

Adverse physicochemical effects:

Vapours are heavier than air, spread along floors and form explosive mixtures with air.

Adverse human health effects and symptoms:

Protect from moisture. Formation of: Methanol. Danger of serious damage to health by prolonged exposure.

Adverse environmental effects:

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

SECTION 3: Composition / information on ingredients

3.2. Mixtures

Hazardous ingredients / Hazardous impurities / Stabilisers:

Product identifiers	Substance name Classification according to Regulation (EC) No. 1272/2008 [CLP]	Concen- tration
CAS No.: 64-17-5 EC No.: 200-578-6 REACH No.: 01-2119457610-43-XXXX	ethanol Flam. Liq. 2, Eye Irrit. 2 The property of the proper	< 70 Wt %
CAS No.: 1185-55-3 EC No.: 214-685-0	trimethoxy(methyl)silane Flam. Liq. 2, Acute Tox. 4 Danger H225-H302	< 10 Wt %
CAS No.: 2943-75-1 EC No.: 220-941-2 REACH No.: 01-2119972313-39-0001	triethoxyoctylsilane Skin Irrit. 2 • Warning H315	< 5 Wt %
CAS No.: 108-88-3 EC No.: 203-625-9	toluene Repr. 2, STOT SE 3, Flam. Liq. 2, Skin Irrit. 2, STOT RE 2, Asp. Tox. 1	< 1 Wt %
CAS No.: 67-56-1 EC No.: 200-659-6	methanol Flam. Liq. 2, Acute Tox. 3, STOT SE 1 Danger H225-H301-H331-H331-H370	< 1 Wt %

Full text of H- and EUH-phrases: see section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information:

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible). Remove victim out of the danger area. Remove contaminated, saturated clothing. If unconscious place in recovery position and seek medical advice. Do not leave affected person unattended. First aider: Pay attention to self-protection!

Following inhalation:

Provide fresh air. In case of respiratory tract irritation, consult a physician.

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 08-May-2015 Print date: 27-May-2015

Version: 1 Page 3/11



HTC Stain Protection

In case of skin contact:

After contact with skin, wash immediately with plenty of water and soap. If skin irritation or rash occurs: Get medical advice/attention.

After eve contact:

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.

After ingestion:

If accidentally swallowed rinse the mouth with plenty of water (only if the person is conscious) and obtain immediate medical attention.

Self-protection of the first aider:

Use personal protection equipment.

4.2. Most important symptoms and effects, both acute and delayed

Serious eye damage/eye irritation

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

Foam, Extinguishing powder, Carbon dioxide (CO2), Water spray

Unsuitable extinguishing media:

Full water jet

5.2. Special hazards arising from the substance or mixture

Vapours are heavier than air, spread along floors and form explosive mixtures with air.

Pyrolysis products, toxic

Hazardous combustion products:

Nitrogen oxides (NOx), Carbon dioxide (CO2), Carbon monoxide.

5.3. Advice for firefighters

Wear a self-contained breathing apparatus and chemical protective clothing.

5.4. Additional information

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water. Dispose of waste according to applicable legislation.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Personal precautions:

Remove persons to safety. Special danger of slipping by leaking/spilling product. Provide adequate ventilation. Remove all sources of ignition.

Protective equipment:

Wear protective gloves/protective clothing/eye protection/face protection.

6.1.2. For emergency responders

Personal protection equipment:

Personal protection equipment: see section 8

6.2. Environmental precautions

Prevent spread over a wide area (e.g. by containment or oil barriers). Do not allow to enter into surface water or drains.

6.3. Methods and material for containment and cleaning up

For containment:

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents).

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 08-May-2015 Print date: 27-May-2015

Version: 1 Page 4/11



HTC Stain Protection

For cleaning up:

Wipe up with absorbent material (eg. cloth, fleece). The contaminated area should be cleaned up immediately with: Solvent

Other information:

Treat the recovered material as prescribed in the section on waste disposal.

6.4. Reference to other sections

Safe handling: see section 7. Personal protection equipment: see section 8. Disposal: see section 13.

6.5. Additional information

Use appropriate container to avoid environmental contamination.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Protective measures

Advices on safe handling:

Wear personal protection equipment (refer to section 8). Provide adequate ventilation. Vapours are heavier than air, spread along floors and form explosive mixtures with air.

Fire prevent measures:

Usual measures for fire prevention. Keep away from sources of ignition. - No smoking. Take precautionary measures against static discharge.

Measures to prevent aerosol and dust generation:

Use only in well-ventilated areas.

Environmental precautions:

Do not allow to enter into surface water or drains.

Advices on general occupational hygiene

Wash hands before breaks and after work. Use protective skin cream before handling the product. When using do not eat, drink or smoke. Avoid contact with skin and eyes.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures and storage conditions:

Keep container tightly closed in a cool, well-ventilated place.

Packaging materials:

Keep/Store only in original container.

Requirements for storage rooms and vessels:

The floor should be leak tight, jointless and not absorbent.

Hints on storage assembly:

Do not store together with: Food and feedingstuffs, Oxidising agent

Storage class: 3 - Flammable liquids

Further information on storage conditions:

Protect containers against damage. Keep away from heat.

7.3. Specific end use(s)

Recommendation:

Observe technical data sheet.

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 08-May-2015 **Print date:** 27-May-2015

Version: 1 Page 5/11



HTC Stain Protection

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1. Occupational exposure limit values

Limit value type (country of origin)	Substance name	 long-term occupational exposure limit value short-term occupational exposure limit value Instantaneous value Monitoring and observation processes remark 	
WEL (GB)	ethanol CAS No.: 64-17-5	① 1,000 ppm (1,920 mg/m³)	
WEL (GB)	toluene CAS No.: 108-88-3	① 50 ppm (191 mg/m³) ② 100 ppm (384 mg/m³)	
IOELV (EU)	toluene CAS No.: 108-88-3	① 50 ppm (192 mg/m³) ② 100 ppm (384 mg/m³) ⑤ (May be absorbed through the skin.)	
WEL (GB)	methanol CAS No.: 67-56-1	① 200 ppm (266 mg/m³) ② 250 ppm (333 mg/m³)	
IOELV (EU)	methanol CAS No.: 67-56-1	① 200 ppm (260 mg/m³) ⑤ (May be absorbed through the skin.)	

8.1.2. biological limit values

No data available

8.1.3. DNEL-/PNEC-values

Substance name	DNEL value	① DNEL type	
		② Exposure route	
ethanol CAS No.: 64-17-5	1,900 mg/m ³	① DNEL worker	
C/13 No.: 04 17 3		② DNEL acute inhalative (local)	
ethanol	950 mg/m ³	① DNEL Consumer	
CAS No.: 64-17-5		② DNEL acute inhalative (local)	
ethanol	950 mg/m ³	① DNEL worker	
CAS No.: 64-17-5		② DNEL long-term inhalative (systemic)	
ethanol	114 mg/m ³	① DNEL Consumer	
CAS No.: 64-17-5		② DNEL long-term inhalative (systemic)	
ethanol	343 mg/kg	① DNEL worker	
CAS No.: 64-17-5	bw/day	② DNEL long-term dermal (systemic)	
ethanol	206 mg/kg	① DNEL Consumer	
CAS No.: 64-17-5	bw/day	② DNEL long-term dermal (systemic)	
ethanol	87 mg/kg	① DNEL Consumer	
CAS No.: 64-17-5	bw/day	② DNEL long-term oral (repeated)	

Substance name	PNEC Value	① PNEC type
ethanol CAS No.: 64-17-5	0.96 mg/l	① PNEC aquatic, freshwater
ethanol CAS No.: 64-17-5	0.79 mg/l	① PNEC aquatic, marine water
ethanol CAS No.: 64-17-5	3.6 mg/kg	① PNEC sediment, freshwater
ethanol CAS No.: 64-17-5	2.9 mg/kg	① PNEC sediment, marine water
ethanol CAS No.: 64-17-5	2.75 mg/l	① PNEC air

en / GB

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 08-May-2015 Print date: 27-May-2015

Version: 1 Page 6/11



HTC Stain Protection

Substance name	PNEC Value	① PNEC type
ethanol CAS No.: 64-17-5	0.63 mg/kg	① PNEC soil, freshwater
ethanol CAS No.: 64-17-5	0.72 mg/kg	① PNEC Secondary Poisoning
ethanol CAS No.: 64-17-5	580 mg/l	① PNEC sewage treatment plant (STP)

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Technical measures to prevent exposure

8.2.2. Personal protection equipment

Eye/face protection:

Eye glasses with side protection

Skin protection:

Tested protective gloves must be worn DIN EN 374. Suitable material: Butyl caoutchouc (butyl rubber). Breakthrough time (maximum wearing time) > 480 min. In the case of wanting to use the gloves again, clean them before taking off and air them well. Breakthrough times and swelling properties of the material must be taken into consideration.

Respiratory protection:

If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn. Respiratory protection necessary at: aerosol or mist formation. Filtering device (full mask or mouthpiece) with filter: A-P2

Other protection measures:

Do not breathe vapour/aerosol. Avoid contact with skin and eyes. Wear suitable protective clothing and gloves.

8.2.3. Environmental exposure controls

See section 7. No additional measures necessary.

8.3. Additional information

No data available

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance

Physical state: liquid Colour: farblos Odour: characteristic

Safety relevant basis data

parameter		at °C	Method	remark
рН	not determined			
Melting point/freezing point	not determined			
Freezing point	not determined			
Initial boiling point and boiling range	≈ 75 °C			
Decomposition temperature (°C):	not determined			
Flash point	12 °C		DIN EN ISO 2719	
Evaporation rate	not determined			
Ignition temperature in °C	≈ 425 °C			
Upper/lower flammability or explosive limits	3.5 - 15 Vol-%			Ethanol
Vapour pressure	not determined			
Vapour density	not determined			
Density	0.88 g/cm ³	20 °C	ISO 2811, part 1	
Bulk density	not determined			

en / GB

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 08-May-2015 **Print date:** 27-May-2015

Version: 1 Page 7/11



HTC Stain Protection

parameter		at °C	Method	remark
Water solubility (g/L)	partially miscible			
Partition coefficient: n-octanol/ water	not determined			
Dynamic viscosity	not determined			
Kinematic viscosity	not determined	40 °C		

9.2. Other information

No data available

SECTION 10: Stability and reactivity

10.1. Reactivity

No hazardous reaction when handled and stored according to provisions.

10.2. Chemical stability

The product is chemically stable under recommended conditions of storage, use and temperature.

10.3. Possibility of hazardous reactions

Exothermic reaction with: Oxidising agent. In use, may form flammable/explosive vapour-air mixture.

10.4. Conditions to avoid

See section 7. No additional measures necessary.

10.5. Incompatible materials

Materials to avoid: Oxidising agent

10.6. Hazardous decomposition products

Gases/vapours, flammable; Formation of: Methanol

SECTION 11: Toxicological information

11.1. Information on toxicological effects

CAS No.	Substance name	Toxicological information
64-17-5	ethanol	LD ₅₀ oral: >2,000 mg/kg (Rat) OECD 401
		LC ₅₀ inhalative: >20 mg/l (Rat)
		LD₅₀ dermal: >2,000 mg/kg (Rabbit) OECD 402
1185-55-3	trimethoxy(methyl)silane	LD₅₀ oral: >11,685 mg/kg (Rat)
		LD₅₀ dermal: >9,500 mg/kg (Rat)
		LC ₅₀ inhalative: >42.1 mg/l (Rat)
2943-75-1	triethoxyoctylsilane	LD₅₀ oral: >5,110 mg/kg (Rat) OECD 401
		LC ₅₀ inhalative: 22 mg/l 4 h (Rat) OECD 403
		LD ₅₀ dermal: 6,730 mg/kg (Rabbit) OECD 402

Acute oral toxicity:

not determined

Acute dermal toxicity:

not determined

Acute inhalation toxicity:

not determined

Skin corrosion/irritation:

not determined

Eye damage/irritation:

Causes serious eye irritation.

Respiratory or skin sensitisation:

not determined

Germ cell mutagenicity:

not determined

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 08-May-2015 Print date: 27-May-2015

Version: 1 Page 8/11



HTC Stain Protection

Carcinogenicity:

not determined

Reproductive toxicity:

not determined

STOT-single exposure:

not determined

STOT-repeated exposure:

not determined

Aspiration hazard:

not determined

Additional information:

The evaluation was carried out according to the calculation method of the preparation directive. Toxicological data are not available.

SECTION 12: Ecological information

12.1. Toxicity

CAS No.	Substance name	Toxicological information	
64-17-5	ethanol	LC ₅₀ : 15,300 mg/l 4 d (Pimephales promelas (fathead minnow))	
		LC ₅₀ : 11,200 mg/l (Salmo gairdneri)	
		EC ₅₀ : 858 mg/l (Artemia salina) OECD 202	
		EC₅₀: >10,000 mg/l 2 d (Daphnia magna (Big water flea))	
		LC ₅₀ : 5,012 mg/l 2 d (Ceriodaphnia dubia)	
		EC ₅₀ : 275 mg/l 3 d (Chlorella vulgaris) OECD 201	
		EC₅₀: 5,800 mg/l (Paramaecium caudatum)	
2943-75-1	triethoxyoctylsilane	EC ₅₀ : >1,000 mg/l (Activated sludge) OECD 209	
		NOEC: ≥1,000 mg/l (Activated sludge) OECD 209	

12.2. Persistence and degradability

CAS No.	Substance name	Biodegradation	remark
64-17-5	ethanol	Yes, rapidly	
2943-75-1	triethoxyoctylsilane	No	

12.3. Bioaccumulative potential

CAS No.	Substance name	Log K _{OC}	Bioconcentration factor (BCF)
64-17-5	ethanol	-0.3	0.66
2943-75-1	triethoxyoctylsilane	6.41	

Accumulation / Evaluation:

No indication of bioaccumulation potential.

12.4. Mobility in soil

No data available

12.5. Results of PBT and vPvB assessment

CAS No.	Substance name	Results of PBT and vPvB assessment
64-17-5	ethanol	_
1185-55-3	trimethoxy(methyl)silane	_
2943-75-1	triethoxyoctylsilane	_
108-88-3	toluene	_
67-56-1	methanol	_

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 08-May-2015 Print date: 27-May-2015

Version: 1 Page 9/11



HTC Stain Protection

12.6. Other adverse effects

The evaluation was carried out according to the calculation method of the preparation directive. Toxicological data are not available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.

13.1.1. Product/Packaging disposal

Waste codes/waste designations according to EWC/AVV

Waste code product:

08 01 11 * Waste paint and varnish containing organic solvents or other dangerous substances

Waste code packaging:

packaging containing residues of or contaminated by dangerous substances

Waste treatment options

Appropriate disposal / Product:

Dispose of waste according to applicable legislation. Consult the appropriate local waste disposal expert about waste disposal.

Appropriate disposal / Package:

Completely emptied packages can be recycled.

13.2. Additional information

No data available

SECTION 14: Transport information

Land transport (ADR/RID)	Inland waterway craft (ADN)	Sea transport (IMDG)	Air transport (ICAO- TI / IATA-DGR)
14.1. UN-No.			
1170	1170	1170	1170
14.2. UN proper ship	ping name		
ETHANOL SOLUTION (ETHYL ALCOHOL SOLU- TION)			
14.3. Transport haza	rd class(es)		
•	•		*
3	3	3	3
14.4. Packing group			
II	II	II	II
14.5. Environmental	hazards		
No	No	No	No

^{*:} Evidence for disposal must be provided.

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 08-May-2015 Print date: 27-May-2015

Version: 1 Page 10/11



HTC Stain Protection

Land transport (ADR/RID)	Inland waterway craft (ADN)	Sea transport (IMDG)	Air transport (ICAO- TI / IATA-DGR)
14.6. Special precau	utions for user		
Special provisions: Limited quantity (LQ): 1 Hazard identification number (Kemler No.): 33 Classification code: F1 tunnel restriction code: D/E	Special provisions: Limited quantity (LQ): 1 Classification code: F1 remark:	Special provisions: Limited quantity (LQ): 1 EmS-No.: F-E; S-D remark:	Special provisions: Limited quantity (LQ): 1 remark:

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code not determined

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU legislation

Other regulations (EU):

91/689/EEC, 2001/118/EC, 1999/13/EC, 2004/42/EC, (EC) No. 1907/2006, (EC) No. 453/2010, 75/324/EEC, 2008/47/EC, (EC) No. 1272/2008, 2008/68/EC, (EC) No. 648/2004

Information according to 1999/13/EC about limitation of emissions of volatile organic compounds (VOC-guideline).: VOC-value (in g/L): 612

Directive 2004/42/EC on the limitation of emissions of volatile organic compounds:

VOC-value (in g/L): 534

This product meets the requirements of Regulation (EC) No. 1935/2004 on the limitation of VOC content.

15.1.2. National regulations

[GB] National regulations

Other regulations, restrictions and prohibition regulations

SI 2002/1689: CHIP Regulations 2002

SI 2002/2677: COSHH Regulations 2002

SI 1999/3242: Management of Health & Safety at Work Regulations 1999

Health & Safety at Work Act 1974

SI 1993/1643: Environmental Protection Act 1993 & Subsidiary Regulations.

Other national and local measures relating to the workplace, pollution control, environmental protection and waste control.

15.2. Chemical Safety Assessment

not applicable

15.3. Additional information

No data available

SECTION 16: Other information

16.1. Indication of changes

No data available

16.2. Abbreviations and acronyms

See overview table at www.euphrac.eu

16.3. Key literature references and sources for data

No data available

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 08-May-2015 Print date: 27-May-2015

Version: 1 Page 11/11



HTC Stain Protection

16.4. Classification for mixtures and used evaluation method according to regulation (EC) 1272/2008 [CLP]

Classification according to Regulation (EC) No. 1272/2008 [CLP]:

Hazard classes and hazard categories		Classification pro- cedure
flammable liquids (Flam. Liq. 2)	H225: Highly flammable liquid and vapour.	
Serious eye damage/eye irritation (Eye Irrit. 2)	H319: Causes serious eye irritation.	

16.5. Relevant R-, H- and EUH-phrases (Number and full text)

Hazard statements		
H225	Highly flammable liquid and vapour.	
H301	Toxic if swallowed.	
H302	Harmful if swallowed.	
H304	May be fatal if swallowed and enters airways.	
H311	Toxic in contact with skin.	
H315	Causes skin irritation.	
H319	Causes serious eye irritation.	
H331	Toxic if inhaled.	
H336	May cause drowsiness or dizziness.	
H361d	Suspected of damaging the unborn child.	
H370	Causes damage to organs.	
H373	May cause damage to organs through prolonged or repeated exposure.	

16.6. Training advice

No data available

16.7. Additional information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.